



Fig. 12 Adjustment coefficient C_R for the wind speed amplification factor R_i

Based on the above statements, the average value of the C_R is determined to be 1.1, and the R_i acquired by the wind environment experiment should be multiplied by the C_R so as to be used in the wind comfort assessment. Therefore, the link of the pedestrian-level R_i between the sub-configuration and the full model is established.

5. Conclusions

In this paper, the pedestrian-level wind environment on the outdoor platforms of a thousand-meter-scale megatall building is studied via the combination of wind tunnel tests and CFD simulations.

The pedestrian-level wind speed amplification factor R_i on the Platform 2 of the sub-configuration acquired by the CFD simulations agree well with the experimental data both in the whole distribution tendency and in the values, so feasibility and credibility of the CFD simulations are validated. Based on the validation, the most unfavorable outdoor platform of the full model with the poorest wind environment is studied via the CFD simulations, and it is determined to be the Platform 4 using the quartiles method in descriptive statistics of the R_i . Besides, an averaged adjustment coefficient $C_R=1.1$ for the R_i is introduced to establish the link of the sub-configuration and the full model, so the R_i for the real megatall building can be calculated by multiplying the experimental data and the above adjustment coefficient C_R , which can be employed for assessment of the pedestrian-level wind comfort and wind danger of the thousand-meter-scale megatall building.

Acknowledgements

The authors want to express their appreciation to the financial support from the China State Construction Engineering Corporation (CSCEC-2010-Z-01-01), the National Natural Science Foundation of China (51108142), and the China Postdoctoral Science Foundation (2013T60377).

REFERENCES

- Bady, M., Kato, S., Ishida, Y., Huang, H., and Takahashi, T. (2011), "Application of exceedance probability based on wind kinetic energy to evaluate the pedestrian level wind in dense urban areas", *Building and Environment*, **46**(9), 1834-1842.
- Blocken, B. and Carmeliet, J. (2004), "Pedestrian wind environment around buildings: Literature review and practical examples", *Journal of Thermal Envelope and Building Science*, **28**(2), 107-159.
- Blocken, B., Roels, S., and Carmeliet, J. (2004), "Modification of pedestrian wind comfort in the Silvertop Tower passages by an automatic control system", *Journal of Wind Engineering and Industrial Aerodynamics*, **92**(10), 849-873.
- Franke, J., Hellsten, A., Schlünzen, H., and Carissimo, B. (2007), "Best practice guideline for the CFD simulation of flows in the urban environment", *COST Action 732*, University of Hamburg, Hamburg, Germany.
- GB50009-2012, 2012, "Load Code for the Design of Building Structures", *China Architecture and Building Press*, Beijing. (in Chinese)
- Hu, C.H., and Wang, F. (2005), "Using a CFD approach for the study of street-level winds in a built-up area", *Building and Environment*, **40**(5), 617-631.
- Kubota, T., Miura, M., Tominaga, Y., and Mochida, A. (2008), "Wind tunnel tests on the relationship between building density and pedestrian-level wind velocity: Development of guidelines for realizing acceptable wind environment in residential neighborhoods", *Building and Environment*, **43**(10), 1699-1708.
- Kuo, C.Y., Tzeng, C.T., Ho, M.C., and Lai, C.M. (2015), "Wind tunnel studies of a pedestrian-level wind environment in a street canyon between a high-rise building with a podium and low-level attached houses", *Energies*, **8**(10), 10942-10957.
- Lawson, T.V. and Penwarden, A.D. (1975), "The effects of wind on people in the vicinity of buildings", in: Proceedings of 4th International Conference on Wind Effects on Buildings and Structures, *Cambridge University Press*, Heathrow, UK, pp. 605-622.
- Livesey, F., Inculet, D., Isyumov, N., and Davenport, A.G. (1993), "A scour technique for the evaluation of pedestrian winds", *Journal of Wind Engineering and Industrial Aerodynamics*, **36**, 779-789.
- Mohan, K., Flay, R.G.J., Gairola A., Kwatra, N., and Mukherjee, M. (2012), "Role of landscape elements in ameliorating adverse pedestrian level winds in the vicinity of tall buildings", *Bonfring International Journal of Industrial Engineering and Management Science*, **2**(4), 41-50.
- Richards, P.J., Mallinson, G.D., Mcmillan, D., and Li, Y.F. (2002), "Pedestrian level wind velocities in downtown Auckland", *Wind and Structures*, **5**, 151-164.
- Shih, T.H., Liou, W.W., Shabbir, A., Yang, Z., and Zhu, J. (1995), "A new $k-\epsilon$ eddy-viscosity model for high Reynolds number turbulent flows: Model development and validation", *Computers and Fluids*, **24**(3), 227-238.
- Soligo, M.J., Irwin, P.A., Williams, C.J., and Schuyler, G.D. (1998), "A comprehensive assessment of pedestrian comfort including thermal effects", *Journal of Wind Engineering and Industrial Aerodynamics*, **77**, 753-766.
- Stathopoulos, T., and Baskaran, B.A. (1996), "Computer simulation of wind environmental conditions around buildings", *Engineering Structures*, **18**(11), 876-885.

- Tominaga, Y., Mochida, A., Yoshie, R., Kataoka, H., Nozu, T., Yoshikawa, M., and Shirasawa, T. (2008), "AIJ guidelines for practical applications of CFD to pedestrian wind environment around buildings", *Journal of Wind Engineering and Industrial Aerodynamics*, **96**, 1749-1761.
- Tsang, C.W., Kwok, K.C.S., and Hitchcock, P.A. (2012), "Wind tunnel study of pedestrian level wind environment around tall buildings: Effects of building dimensions, separation and podium", *Building and Environment*, **49**, 167-181.
- Tu, J.Y., Yeoh, G.H., and Liu, C.Q. (2008), "Computational fluid dynamics: A practical approach", *Butterworth-Heinemann: Burlington, USA*.
- Williams, C.D., and Wardlaw, R.L. (1992), "Determination of the pedestrian wind environment in the city of Ottawa using wind tunnel and field measurements", *Journal of Wind Engineering and Industrial Aerodynamics*, **41**(1-3), 255-266.
- Wu, H., and Stathopoulos, T. (1994), "Further experiments on Irwin's surface wind sensor", *Journal of Wind Engineering and Industrial Aerodynamics*, **53**(3), 441-452.
- Youssef, S.W. (1998), "Experimental evaluation of pedestrian-level winds", *University of Minnesota*.
- Zhang, A., Gu, M., and Zhang, L. (2007), "Computer simulation of pedestrian wind environment around buildings", *Journal of Tongji University (Natural Science)*, **35**(8), 1030-1033. (in Chinese)
- Zheng, C.R., and Zhang, Y.C. (2012), "Computational fluid dynamics study on the performance and mechanism of suction control over a high-rise building", *The structural design of tall and special buildings*, **21**, 475-491.